



**Compostex® Windrow Covers - Specifications/Pricing 2019**

Item	Details
Color	Black
Type	Needle-punch/Non-woven
Thickness	1.8 mm±
Fibers	Polypropylene/U.V. Resistant
Tensile Strength – ONCG 148, 1-7	500N
Elongation	70% -100%
Tear Strength	250N
Mullen Burst – ONGC 2-4.2-M77-11.1	1200 kPa
Streaming	20 grams of water
Air Permeability – ONGC 148.1-4	425-500 C.F.M.
Weight	200 g/m2 ±15 g/m2
Porosity	90 – 110 microns
Finish Treatment	Thermal Stabilization
<b>2019 Pricing: CDN Currency</b>	
12 ft (3.66 m) width	\$ 5.00 linear ft., \$16.25 linear meter
15 ft (4.57 m) width	\$ 5.95 linear ft., \$19.50 linear meter
18 ft (5.54 m) width	\$ 6.75 linear ft., \$21.50 linear meter
24 ft (7.32m) width	\$ 8.75 linear ft., \$28.50 linear meter
30 ft (9.14m) width	\$11.00 linear ft., \$35.00 linear meter
36 ft (10.97m)width	\$13.00 linear ft., \$42.00 linear meter
48 ft (14.64 m) width	\$17.25 linear ft., \$56.25 linear meter

Prices are Ex-Works our location.

Compostex is produced as ordered and available in lengths up to 480 ft(150 meters) depending on width as weight can be a factor.

Available in up to 72' (21.96 m) widths upon request.

01/19